

ORALIGHT® TRANSPARENT / CHROME / OPAQUE

ORALIGHT® code #31

Weighing only 36 g/m² INCLUDING thermo-active adhesive **ORALIGHT®** is an absolute lightweight. **ORALIGHT®** is the ideal solution if you need to reduce the weight of your construction to a minimum. **ORALIGHT®** shares the superior qualities of **ORACOVER®**. Standard roll lengths: 2 m, 10 m, 20 m, 50 m, 100 m, 150 m, 250 m. Width: 60 cm.

ORALIGHT® TRANSPARENT / CHROME		
colour	ORALIGHT®	ORALIGHT®
	2m-rolls	10m-rolls
light transparent	31-000-002	31-000-010
light transp. white	31-010-002	31-010-010
light transp. red	31-029-002	31-029-010
light transp. yellow	31-039-002	31-039-010
light transp. purple	31-058-002	31-058-010
light transp. blue	31-059-002	31-059-010
light chrome	31-090-002	31-090-010
light chrome red	31-093-002	31-093-010
light chrome yellow	31-094-002	31-094-010
light chrome violet	31-096-002	31-096-010
light chrome blue	31-097-002	31-097-010
light scale white	31-099-002	31-099-010



ORALIGHT® OPAQUE		
colour	ORALIGHT®	ORALIGHT®
	2m-rolls	10m-rolls
white	31-110-002	31-110-010
grey	31-011-002	31-011-010
cream	31-012-002	31-012-010
olive drab	31-018-002	31-018-010
corsair blue	31-019-002	31-019-010
red	31-020-002	31-020-010
bright red	31-022-002	31-022-010
ferri red	31-023-002	31-023-010
cub yellow	31-030-002	31-030-010
cadmium yellow	31-033-002	31-033-010
blue	31-050-002	31-050-010
dark blue	31-052-002	31-052-010
orange	31-060-002	31-060-010
black	31-071-002	31-071-010
brown	31-081-002	31-081-010
silver	31-091-002	31-091-010
effect silver	31-191-002	31-191-010

Technical data of: **ORALIGHT®**

- **Material thickness total (supporting film):** approx. 22 µm (approx. 12 µm) - **Weight:** approx. 36 g/m² - **Tensile strength (lengthwise and crosswise):** mind. 150 N / 50 mm - **Breaking extension (lengthwise and crosswise):** mind. 90 %
- **Adhesive power:** mind. 7 N / 25 mm - **Shrinkage:** mind. 5 % in both directions (reference temperature 150 °C) - **Melting point:** 250 °C